



**SACCAL INDUSTRIES S.A.L.**  
Member of Saccal Holding

## PL 275

Engine Perkins, 1206A-E88TAG3

### STANDARD FEATURES

- Water cooled PERKINS diesel engine.
- Radiator with pressure cap and drain point
- Fully guarded engine-driven fan
- Fully welded steel skid base with lifting points
- Heavy duty rubber anti-vibration mountings
- 24V starter batteries and connecting cables
- Separate engine-driven battery charging alternator
- Spin on oil and fuel filters and dry type air filter element



Voltage	Standby Power KVA	Prime Power KVA	Stand by Amps	Dimensions	Weight
415 / 240	275	250	382.6	L x W x H = 2500 x 1000 x 1800 mm	2715 Kg.
400 / 230	275	250	396.9		
380 / 220	275	250	417.8		

#### POWER DEFINITION

**Prime Power** is available for an unlimited number of annual operating hours in variable load applications

**Standby Power** is applicable for supplying emergency power in variable load applications

#### TERMS OF USE

Standard reference conditions Standby / Prime 27°C / 40°C Air Inlet Temp, 1000 m / 1000 m A.S.L. 60% relative humidity.

#### Main features:

- Heavy level acoustic attention: 65 dB at 1 meter from all directions on site
- A critical type muffler is mounted inside the enclosure
- Total design flexibility
- Robustness and enhanced durability
- Heavy duty base frame made up of steel U channels 10\*5cm insulated with 10cm sound absorbing material and covered by 2, 3mm sheet steel from both sides up and down
- Canopy components are manufactured in 1.5, 2, 3mm sheet steel
- Canopy walls and ceiling are coated with sound absorbing material
- Anti Scratch 100 micron Powder Paint Coated under the temperature of 120 oC
- Four lockable doors
- Four lifting points
- Oil and coolant drainage points
- Easy canopy dismantling for maintenance purpose
- Full weather proof enclosure



#### Dimensions Super Sound Proof Version

Canopy	SSP275
Length (mm).	3500
Width (mm).	1140
Height (mm).	2060
Dry weight (kg).	N/A

This document is not contractual – Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.

Saccal Industries S.A.L. – Taanayel – Bekaa – Lebanon.  
Tel +961 (8) 51 01 57 – Fax : +961 (8) 51 01 58 – [www.saccal.com](http://www.saccal.com)



## ENGINE SPECIFICATIONS

<b>DATA</b>  <b>GENERAL DATA</b>	Motor model	<b>Perkins 1506A-E88TAG3, 6 cylinders</b>
	Cylinder arrangement	Vertical in-line
	Displacement (L)	8.8
	Bore (in) X Stroke (in)	112 mm x 149 mm
	Compression ratio	16.1:1
	Speed (RPM)	1500
	Cycle	4 Stroke
	Maximum stand-by power at rated RPM (KWm)	244
	BMEP (psi)	NA
	Governor type	ELECTRONIC
<b>EXHAUST SYSTEM</b>	Exhaust gas temperature (°C)	640
	Exhaust gas flow (cfm)	1567
	Max. exhaust back pressure (mmWG)	500
<b>FUEL SYSTEM</b>	Consumption @ 110% load (L/hr)	
	Consumption @ 100% load (L/hr)	
	Consumption @ 75% load (L/hr)	42
	Consumption @ 50% load (L/hr)	
<b>OIL</b>	Oil capacity (L)	26.4
	Min. oil pressure (Bar)	4.7
	Max. oil pressure (Bar)	7.5
	Oil consumption 100% load (L/hr)	N/A
<b>THERMAL BALANCE</b>	Heat rejection to exhaust (KW)	213
	Radiated heat to ambient (KW)	34
	Heat rejection to coolant (kW)	158
<b>AIR INTAKE</b>	AIR INTAKE_entree_max% Intake air flow (L/sec)	NA
<b>COOLANT SYSTEM</b>	Radiator & Engine capacity (L)	37.2
	Max water temperature (°C)	102
	Outlet water temperature (°C)	95
	Fan power (kW)	5.4
	Fan air flow w/o restriction (m3/sec)	5.5
	Available restriction on air flow (mm WG)	20
	Type of coolant Thermostat (°C)	Gencool 82-95
<b>EMISSIONS</b>	Emissions PM (g/kW.h)	NA
	Emission CO (g/kW.h)	NA
	Emissions HCNOx (g/kWh)	NA
	Emission HC (g/kW.h)	NA

This document is not contractual –Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.