



**SACCAL INDUSTRIES S.A.L.**  
Member of Saccal Holding

# PN 15

Engine Perkins, 403A-15G1

## STANDARD FEATURES

- Water cooled PERKINS diesel engine.
- Radiator with pressure cap and drain point
- Fully guarded engine-driven fan
- Fully welded steel skid base with lifting points
- Heavy duty rubber anti-vibration mountings
- 12V starter batteries and connecting cables
- Separate engine-driven battery charging alternator
- Spin on oil and fuel filters and dry type air filter element



Voltage	Standby Power KVA	Prime Power KVA	Stand by Amps	Dimensions	Weight
415 / 240	15	13	20.9	L x W x H = 1250 x 650 x 960 mm	400 Kg.
400 / 230	15	13	21.6		
380 / 220	15	13	22.8		

### POWER DEFINITION

**Prime Power** is available for an unlimited number of annual operating hours in variable load applications

**Standby Power** is applicable for supplying emergency power in variable load applications

### TERMS OF USE

Standard reference conditions Standby / Prime 27°C / 40°C Air Inlet Temp, 1000 m / 1000 m, 60% relative humidity.



### Main features:

- Heavy level acoustic attention: 65 dB at 1 meter from all directions on site
- A critical type muffler is mounted inside the enclosure
- Total design flexibility
- Robustness and enhanced durability
- Heavy duty base frame made up of steel U channels 10\*5cm insulated with 10cm sound absorbing material and covered by 2, 3mm sheet steel from both sides up and down
- Canopy components are manufactured in 1.5, 2, 3mm sheet steel
- Canopy walls and ceiling are coated with sound absorbing material
- Anti Scratch 100 micron Powder Paint Coated under the temperature of 120 oC
- Four lockable doors
- Four lifting points
- Oil and coolant drainage points
- Easy canopy dismantling for maintenance purpose
- Full weather proof enclosure

### Dimensions Super Sound Proof Version

Canopy	SSP15
Length (mm).	2450
Width (mm).	870
Height (mm).	1400
weight (kg).	750

This document is not contractual –Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.

Saccal Industries S.A.L. – Taanayel – Bekaa – Lebanon.  
Tel +961 (8) 51 01 57 – Fax : +961 (8) 51 01 58 – [www.saccal.com](http://www.saccal.com)



## ENGINE SPECIFICATIONS

DATA  GENERAL DATA	Motor model	Perkins 403A-15G1, 3 cylinders
	Cylinder arrangement	Vertical in-line
	Displacement (L)	1.496
	Bore (in) X Stroke (in)	84 mm x 90 mm
	Compression ratio	22.5:1
	Speed (RPM)	1500
	Cycle	4 Stroke
	Maximum stand-by power at rated RPM (BHP)	18.1
	BMEP (psi)	NA
	Governor type	MECHANICAL
EXHAUST SYSTEM	Exhaust gas temperature (°C)	590
	Exhaust gas flow (cfm)	115
	Max. exhaust back pressure (mmWG)	500
FUEL SYSTEM	Consumption @ 110% load (L/hr)	
	Consumption @ 100% load (L/hr)	
	Consumption @ 75% load (L/hr)	2.8
	Consumption @ 50% load (L/hr)	
OIL	Oil capacity (L)	6
	Min. oil pressure (Bar)	4.7
	Max. oil pressure (Bar)	7.5
	Oil consumption 100% load (L/hr)	0.3
THERMAL BALANCE	Heat rejection to exhaust (KW)	15
	Radiated heat to ambient (KW)	2
	Heat rejection to coolant (kW)	18.6
AIR INTAKE	AIR INTAKE_entree_max% Intake air flow (L/sec)	NA
COOLANT SYSTEM	Radiator & Engine capacity (L)	6
	Max water temperature (°C)	102
	Outlet water temperature (°C)	95
	Fan power (kW)	1.8
	Fan air flow w/o restriction (m3/sec)	0.9
	Available restriction on air flow (mm WG)	10
	Type of coolant Thermostat (°C)	Gencool 82-95
EMISSIONS	Emissions PM (g/kW.h)	NA
	Emission CO (g/kW.h)	NA
	Emissions HCNOx (g/kWh)	NA
	Emission HC (g/kW.h)	NA

This document is not contractual –Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.