



# PL 385

Engine Perkins, 2206A-E13TAG2

## STANDARD FEATURES

- Water cooled PERKINS diesel engine.
- Radiator with pressure cap and drain point
- Fully guarded engine-driven fan
- Fully welded steel skid base with lifting points
- Heavy duty rubber anti-vibration mountings
- 24V starter batteries and connecting cables
- Separate engine-driven battery charging alternator
- Spin on oil and fuel filters and dry type air filter element



Voltage	Standby Power KVA	Prime Power KVA	Stand by Amps	Dimensions	Weight
415 / 240	385	350	535.6	L x W x H = 3200 x 1140 x 2000 mm	2715 Kg.
400 / 230	385	350	555.7		
380 / 220	385	350	584.9		

### POWER DEFINITION

**Prime Power** is available for an unlimited number of annual operating hours in variable load applications

**Standby Power** is applicable for supplying emergency power in variable load applications

### TERMS OF USE

Standard reference conditions Standby / Prime 27°C / 40°C Air Inlet Temp, 1000 m / 1000 m A.S.L. 60% relative humidity.



### Main features:

- Heavy level acoustic attention: 65 dB at 1 meter from all directions on site
- A critical type muffler is mounted inside the enclosure
- Total design flexibility
- Robustness and enhanced durability
- Heavy duty base frame made up of steel U channels 10\*5cm insulated with 10cm sound absorbing material and covered by 2, 3mm sheet steel from both sides up and down
- Canopy components are manufactured in 1.5, 2, 3mm sheet steel
- Canopy walls and ceiling are coated with sound absorbing material
- Anti-Scratch 100 micron Powder Paint Coated under the temperature of 120 oC
- Four lockable doors
- Four lifting points
- Oil and coolant drainage points
- Easy canopy dismantling for maintenance purpose
- Full weather proof enclosure
- Suitable for operation in very adverse weather conditions

### Dimensions Super Sound Proof Version

Canopy	SSP385
Length (mm).	4200
Width (mm).	1320
Height (mm).	2500
Dry weight (kg).	N/A

This document is not contractual – Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.



## ENGINE SPECIFICATIONS

		Perkins 2206A-E13TAG2, 6 cylinders
DATA  GENERAL DATA	Motor model	
	Cylinder arrangement	Vertical in-line
	Displacement (L)	12.5
	Bore (in) X Stroke (in)	130 mm x 157 mm
	Compression ratio	16.3:1
	Speed (RPM)	1500
	Cycle	4 Stroke
	Maximum stand-by power at rated RPM (BHP)	493
	BMEP (psi)	NA
Governor type	ELECTRONIC	
EXHAUST SYSTEM	Exhaust gas temperature (°C)	519
	Exhaust gas flow (cfm)	1642
	Max. exhaust back pressure (mmWG)	500
FUEL SYSTEM	Consumption @ 110% load (L/hr)	
	Consumption @ 100% load (L/hr)	
	Consumption @ 75% load (L/hr)	54
	Consumption @ 50% load (L/hr)	
OIL	Oil capacity (L)	40
	Min. oil pressure (Bar)	4.7
	Max. oil pressure (Bar)	7.5
	Oil consumption 100% load (L/hr)	N/A
THERMAL BALANCE	Heat rejection to exhaust (KW)	224
	Radiated heat to ambient (KW)	9
	Heat rejection to coolant (kW)	129
AIR INTAKE	AIR INTAKE_entree_max% Intake air flow (L/sec)	NA
COOLANT SYSTEM	Radiator & Engine capacity (L)	51.4
	Max water temperature (°C)	102
	Outlet water temperature (°C)	95
	Fan power (kW)	10.3
	Fan air flow w/o restriction (m3/sec)	5.9
	Available restriction on air flow (mm WG)	20
	Type of coolant Thermostat (°C)	Gencool 82-95
EMISSIONS	Emissions PM (g/kW.h)	NA
	Emission CO (g/kW.h)	NA
	Emissions HCNOx (g/kWh)	NA
	Emission HC (g/kW.h)	NA

This document is not contractual – Saccal Industries company reserves the right to modify any of the characteristics stated in this data sheet without notice in a constant effort to improve the quality of its products.