

Ratings @ 0.8 PF 50 Hz 1500 RPM

VOLTAGE	PRIME RATING	STANDBY RATING
400/3 Ph	20 KVA	22 KVA

NOTES

Prime Power

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period.

A 10% overload is available for 1 hour in every 12 hour operation.

Standby Power

Limited to 500 hours annual usage

Available in 60HZ for all voltage ratings

Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air inlet temp, 100m (328 ft.) A.S.L. 30% relative humidity.

Standards Compliance



Dimensions

	Open Type	Silent	Super Silent
Length:	1350mm	2280mm	3520mm
Width:	750mm	940mm	1070mm
Height:	1200mm	1280mm	1560mm
Weight:	500kg	840kg	1100kg





71



Technical Data

Diesel Generating Set

GENSET Make / Model	Baudoin 4M06C25/5
Alternator Make / Model	Leroy Somer TAL 040F
Control Panel	DSE 4520
Base Frame / Canopy	Robust Structure / Corrosion Resistant
Circuit Breaker Type	3-Pole MCCB (4-Pole Available as option)
Built-In Fuel Tank Capacity (Silent)	50L
Battery	1 X 50A

Engine Specifications

Make & Model	Baudoin 4M06G25/5
Cylinder & Arragement	4; In Line
Cycle	4 stroke
Induction System / Aspiration	Natural
Cooling System	Water cooled
Governing	Electronic
Governing Class	ISO 8528-5 Class G3
Compression Ratio	17.5:1
Displacement	2.3
Bore & Stroke	89 x 92 mm
Dynamic Charging Alternator	55 AMP, 12V

Lubrication System

Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	7.1 L
Oil Type	15w40

Cooling System

Total Coolant Capacity	3.2 L
Cooling Fan Air Flow	48 m3/s
Max Water Temperature	98°C

Air System

Air Filter Type	Dry Element
Max Air Filter Intake Restriction	35 mBar

Cooling System Design 50°C

Heat Radiation to 3.5 kJ/s Room

Exhaust System

Muffler Type	Industrial Grade
Max Back Pressure	80 mBar
Exhaust Gas Flow	5.32 m3 / min
Exhaust Gas Temperature	≤700° C



LEBANON BEIRUT

Rachid Karami st, Concorde Center Telephone: +961 1 34 45 18 E-mail: industries@saccal.com

UAE SHARJAH

Business center, SPC, Publishing City Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com

IRAQ ERBIL

Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846

BAGHDAD

Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com











Engine Fuel System

Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	7.1 L/hr
Fuel Consumption @100% PRP	6.1 L/hr
Fuel Consumption @75% PRP	4.5 L/hr
Eucl Consumption @50% BBB	321/br

Alternator Specifications

Alternator Make / Model	Leroy Somer TAL 040F
AVR Model	R120
Number of Poles	
Number of Winding Leads	6
Type of Bearing	Single Bearing
Excitation System	Self Excited
Ingress Protection Rating	IP23
Cooling Airflow	0.06 m3 / Sec
Voltage Regulation	±1%
Harmonic Coefficient THF	< 2%
Tel. Influence TIF	< 50
Insulation Class	Н







Engine



Alternator



Saccal Enclosure / Canopy

Controller Make / Model	DeepSea 4520
Operation Mode	Auto-Start & AMF
Display	Graphic Backlit LCD (128x64px)
Ingress Protection Rating	IP65
Binery Inputs/Outputs	4/4
Analog Inputs	3
Measurements	Vac, A, Hz, KVA,KW, Vdc
Event Log	Alarms Log, Hrs Log
Communication	USB

Сапору Туре	SILENT SUPER SILENT
Enclosure Type	Acoustic & Weather Proof
Drainage	Fuel and Water Drainage Provision
Transportation	Tested Single Point Lifting Facility & Forklift Pockets
Ingress Protection	IP23
Lifting	ISO Standard Lifting
Canopy RAL Color	RAL 9002 - Powder Coated
Base Frame RAL Color	RAL 9005 - Powder Coated
Noise Pressure Level db(A) @ 1m @75% Load	71 65

SACCAL TOOL BOX

Standard for every GenSet

- Heat Resistant Gloves
- Notebook
- Pen
- Tape Measure
- Baseball Cap
- Owner & Operation Manual
- · Wiring Diagrams
- Sound Test (Upon Request)

Why Saccal Generators?

Saccal Industries is one of the leading Diesel Generator OEM firms in the **MENA** Region

With an impressive Factory that spreads over an area of 30 thousand square meters in Bekaa & ISO certification, SACCAL has always been the leading name in the manufacturing and assembly of premium quality generating sets.

From planning and design, construction and production, to local and international sales, Saccal Has more than 80 Years of experience.

Choose Right - Choose Saccal



Rachid Karami st, Concorde Center Telephone: +9611344518 E-mail: industries@saccal.com

UAE SHARJAH

E6 - 024 - Safezone Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com

IRAQ ERBIL

Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846

BAGHDAD

Riyadh District Square - District 908 Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com

