BN 33

STAMFURU

power generation

Baudouin

T

.

(T)



Ratings @ 0.8 P		50 Hz 600 RPM
VOLTAGE	PRIME RATING	STANDBY RATING
400/3 Ph	30 KVA	33 KVA

NOTES

Prime Power

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period.

A 10% overload is available for 1 hour in every 12 hour operation.

Standby Power

Limited to 500 hours annual usage

Available in 60HZ for all voltage ratings

Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air inlet temp, 100m (328 ft.) A.S.L. 30% relative humidity.

Standards Compliance



	Dimo		
	Open Type	Silent	Super Silent
Length:	1450mm	2280mm	3520mm
Width:	800mm	1000mm	1070mm
Height:	1250mm	1480mm	1560mm
Weight:	550kg	1290kg	1400kg

Technical Data

Diesel Generating Set

GENSET Make / Model	Baudoin 4M06G35/5
Alternator Make / Model	Stamford Tech 184CS
Control Panel	DSE 7320
Base Frame / Canopy	Robust Structure / Corrosion Resistant
Circuit Breaker Type	3-Pole MCCB (4-Pole Available as option)
Built-In Fuel Tank Capacity (Silent)	100L
Battery	70A

Gensets

Small Range

Engine Specifications

Make & Model	Baudoin 4M06G35/5
Cylinder & Arragement	4; In Line
Cycle	4 stroke
Induction System / Aspiration	Turbocharged
Cooling System	Water cooled
Governing	Electronic
Governing Class	ISO 8528-5 Class G3
Compression Ratio	17.5 : 1
Displacement	2.3
Bore & Stroke	82 x 92 mm
Dynamic Charging Alternator	55 AMP, 12V

Lubrication System

Oil Filter Type	Spin-On Full Flow	
Total Oil Capacity	9.5 L	
Oil Type	15w40	

Cooling System

Total Coolant Capacity Cooling Fan Air Flow 48 m3/s Max Water Temperature

Air System

States and the states	
Filter Type	Dry Element
x Air Filter Intake striction	35 mBar

UAE

Cooling System Design 50°C

Heat Radiation to Room

3.9 kJ/s

Exhaust System

Muffler Type	Industrial Grade		
Max Back Pressure	80 mBar		
Exhaust Gas Flow	6.48		
Exhaust Gas Temperature	≤700° C		



LEBANON BEIRUT Rachid Karami st, Concorde Center

Telephone: +9611344518 E-mail: industries@saccal.com

Max Res

SHARJAH

Business center, SPC, Publishing City Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com

ERBIL Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846 +964 77 09887972 E-mail: erbil@saccal.com

IRAQ

BAGHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com



BN 33

****		Genset ^{Small Rang}		n STAMFORD power generation
* 1944 * *	Engine Fue	el System	Alternator	Specifications
* * Since *	Recommended Fuel	Class A2 Diesel	Alternator Make / Model	Stamford Tech 184GS
	Fuel Consumption Standby	8.4 L/hr	AVR Model	SX460
5/IGE/IE	Fuel Consumption @100% PRP	7.6 L/hr	Number of Poles	4
	Fuel Consumption @75% PRP	5.7 L/hr	Number of Winding Leads	6
	Fuel Consumption @50% PRP	4.0 L/hr	Type of Bearing	Single Bearing
			Excitation System	Self Excited
	ccal.		Ingress Protection Rating	IP23
			Cooling Airflow	0.095 m3 / Sec
			Voltage Regulation	±1%
			Harmonic Coefficient THF	< 2%
			Tel. Influence TIF	< 50
Image: Controller	Contraction of the second seco	Alternator	Saccal Encle	osure / Canopy
Controller Make / Model	DeepSea 7320	Canopy Type	SILENT	SUPER SILENT
Operation Mode	Auto-Start & AMF	Enclosure Type	Acoustic & Wea	ther Proof
Display	Graphic Backlit LCD (128x64px)	Drainage	Fuel and Water	Drainage Provision
Ingress Protection Rating	IP65	Transportation	Tested Single P Forklift Pockets	oint Lifting Facility &
Binery Inputs/Outputs	4/4	Ingress Protection	IP23	
Analog Inputs	3	Lifting	ISO Standard L	ifting
Measurements	Vac, A, Hz, KVA,KW, Vdc	Canopy RAL Color	RAL 9002 - Pov	vder Coated

Alarms Log, Hrs Log Event Log Communication

SACCAL TOOL BOX

Standard for every GenSet

- Heat Resistant Gloves
- Notebook
- Pen
- Tape Measure
- **Baseball** Cap .
- Owner & Operation Manual
- Wiring Diagrams
- Sound Test (Upon Request)

Why Saccal Generators ?

Base Frame RAL Color

Noise Pressure Level db(A) @ 1m @75% Load

Saccal Industries is one of the leading Diesel Generator OEM firms in the **MENA** Region

With an impressive Factory that spreads over an area of 30 thousand square meters in Bekaa & ISO certification, SACCAL has always been the leading name in the manufacturing and assembly of premium quality generating sets.

From planning and design, construction and production, to local and international sales, Saccal Has more than 80 Years of experience.

Choose Right - Choose Saccal

SACCAL

LEBANON BEIRUT Rachid Karami st, Concorde Center Telephone: +9611344518 **INDUSTRIES** E-mail: industries@saccal.com

UAE SHARJAH E6 - 024 - Safezone Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com IRAQ ERBIL Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846 +964 77 09887972 E-mail: erbil@saccal.com

BAGHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com

RAL 9005 - Powder Coated

