# **BN 55**

STAMFURU

power generation

Baudouin

E

.

(T)



Ratings @ 0.8 P		50 Hz 600 RPM
VOLTAGE	PRIME RATING	STANDBY RATING
400/3 Ph	50 KVA	55 KVA

### NOTES

#### **Prime Power**

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period.

A 10% overload is available for 1 hour in every 12 hour operation.

#### **Standby Power**

Limited to 500 hours annual usage

Available in 60HZ for all voltage ratings

#### Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air inlet temp, 100m (328 ft.) A.S.L. 30% relative humidity.

### Standards Compliance



	Dimo		
	Open Type	Silent	Super Silent
Length:	1650mm	2280mm	3520mm
Width:	800mm	1000mm	1070mm
Height:	1250mm	1480mm	1560mm
Weight:	580kg	1320kg	1560kg

**Technical Data** 

### **Diesel Generating Set**

GENSET Make / Model	Baudoin 4M06G55/5
Alternator Make / Model	Stamford Tech 224DS
Control Panel	DSE 4520
Base Frame / Canopy	Robust Structure / Corrosion Resistant
Circuit Breaker Type	3-Pole MCCB (4-Pole Available as option)
Built-In Fuel Tank Capacity (Silent)	100L
Battery	1 X 70A

Gensets

Small Range

### **Engine Specifications**

Make & Model	Baudoin 4M06G55/5
Cylinder & Arragement	4; In Line
Cycle	4 stroke
Induction System / Aspiration	Turbocharged
Cooling System	Water cooled
Governing	Electronic
Governing Class	ISO 8528-5 Class G3
Compression Ratio	17.5 : 1
Displacement	2.3
Bore & Stroke	89 x 92 mm
Dynamic Charging Alternator	50 AMP, 12V

## **Lubrication System**

Oil Filter Type	Spin-On Full Flow
Total Oil Capacity	7.35 L
Oil Type	15w40

## **Cooling System**

**Total Coolant Capacity Cooling Fan Air Flow** 102 m3/s Max Water Temperature

## Air System

Filter Type	Dry Element
x Air Filter Intake striction	35 mBar

UAE

### Cooling System Design 50°C

Heat Radiation to Room

3.9 kJ/s

### **Exhaust System**

Muffler Type	Industrial Grade
Max Back Pressure	80 mBar
Exhaust Gas Flow	5.32 m3 / min
Exhaust Gas Temperature	≤700° C



#### LEBANON BEIRUT Rachid Karami st, Concorde Center

Telephone: +9611344518 E-mail: industries@saccal.com

Max Res

SHARJAH

ERBIL Business center, SPC, Publishing City Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com

IRAQ

Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846 +964 77 09887972 E-mail: erbil@saccal.com

BAGHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com



# BN55

*****		Genset <sup>Small Rang</sup>		n STAMFORD power generation
* 1944 *	Engine Fue	el System	Alternator	Specifications
* * * Since *	Recommended Fuel	Class A2 Diesel	Alternator Make / Model	Stamford Tech 224DS
	Fuel Consumption Standby	13.3 L/hr	AVR Model	SX460
5/166/16	Fuel Consumption @100% PRP	11.9 L/hr	Number of Poles	4
	Fuel Consumption @75% PRP	8.9 L/hr	Number of Winding Leads	6
	Fuel Consumption @50% PRP	6.0 L/hr	Type of Bearing	Single Bearing
			Excitation System	Self Excited
	cal		Ingress Protection Rating	IP23
			Cooling Airflow	0.216 m3 / Sec
			Voltage Regulation	±1%
			Harmonic Coefficient THF	< 2%
			Tel. Influence TIF	< 50
Image: Controller	Finging	Alternator	Saccal Encl	osure / Canopy
Controller Make / Model	DeepSea 4520	Canopy Type	SILENT	SUPER SILENT
Operation Mode	Auto-Start & AMF	Enclosure Type	Acoustic & Wea	ather Proof
Display	Graphic Backlit LCD (128x64px)	Drainage	Fuel and Wate	r Drainage Provision
Ingress Protection Rating	IP65	Transportation	Tested Single F Forklift Pockets	Point Lifting Facility & s
Binery Inputs/Outputs	4/4	Ingress Protection	IP23	
Analog Inputs	3	Lifting	ISO Standard L	ifting

 Measurements
 Vac, A, Hz, KVA, KW, Vdc

 Event Log
 Alarms Log, Hrs Log

 Communication
 USB

SACCAL TOOL BOX

Standard for every GenSet

Owner & Operation Manual

Sound Test (Upon Request)

• Heat Resistant Gloves

Notebook

Tape Measure

**Baseball** Cap

Wiring Diagrams

Pen

.

Why Saccal Generators ?

Canopy RAL Color

**Base Frame RAL Color** 

Noise Pressure Level db(A) @ 1m @75% Load

# **Saccal Industries** is one of the leading Diesel Generator OEM firms in the **MENA** Region

With an impressive Factory that spreads over an area of 30 thousand square meters in Bekaa & ISO certification, SACCAL has always been the leading name in the manufacturing and assembly of premium quality generating sets.

From planning and design, construction and production, to local and international sales, Saccal Has more than 80 Years of experience.

### Choose Right - Choose Saccal

SACCAL INDUSTRIES

LEBANON BEIRUT Rachid Karami st, Concorde Center Telephone: +9611344518 E-mail: Industries@eaccal.com UAE SHARJAH E6 - 024 - Safezone Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com IRAQ ERBIL Street 100 - 3/57, Warsh Telephone: +964 77 09887972 E-mail: erbil@saccal.com

BACHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com

RAL 9002 - Powder Coated

RAL 9005 - Powder Coated

