# BN 880

STAMFURU

power generation

Baudouin

.



Ratings @ 0.8 P		50 Hz 1500 RPM		
VOLTAGE	PRIME RATING	STANDBY RATING		
400/3 Ph	800 KVA	880 KVA		

### NOTES

### **Prime Power**

Unlimited hours usage with an average load factor of 80% of the published Prime power over each 24 hours period.

A 10% overload is available for 1 hour in every 12 hour operation.

### **Standby Power**

Limited to 500 hours annual usage

Available in 60HZ for all voltage ratings

### Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air inlet temp, 100m (328 ft.) A.S.L. 30% relative humidity.

### Standards Compliance



	Open Type	Silent	Super Silent
Length:	4300mm	6050mm	12190mm
Width:	1700mm	2440mm	2440mm
Height:	2250mm	2440mm	2590mm
Weight:	5000kg	11700kg	16800kg

Technical Data

### **Diesel Generating Set**

GENSET Make / Model	Baudoin 12M26C900/5
Alternator Make / Model	Stamford Tech 404C
Control Panel	DSE 7320
Base Frame / Canopy	Robust Structure / Corrosion Resistant
Circuit Breaker Type	3-Pole MCCB (4-Pole Available as option)
Built-In Fuel Tank Capacity (Silent)	N/A
Battery	2 x 150A

Gensets

Large Range

### **Engine Specifications**

Make & Model	Baudoin 12M26G900/5
Cylinder & Arragement	12; V Form
Cycle	4 stroke
Induction System / Aspiration	Turbocharged
Cooling System	Water cooled
Governing	Electronic
Governing Class	ISO 8528-5 Class G3
Compression Ratio	15.7 : 1
Displacement	31.8
Bore & Stroke	150 x 185 mm
Dynamic Charging Alternator	55 AMP, 24V

# **Lubrication System**

Oil Filter Type	Spin-On Full Flow	
Total Oil Capacity	109.0 L	
Oil Type	15w40	

# **Cooling System**

Total Coolant Capacity	71.0 L	
Cooling Fan Air Flow	1044 m3/s	
Max Water Temperature	98°C	

## Air System

a substantia a subst
Dry Element
30 mBar

### Cooling System Design 50°C

Heat Radiation to Room

o 93.6 kJ/s

# Exhaust System

# Muffler Type Industrial Grade Max Back Pressure 75 mBar Exhaust Gas Flow 175.1 m3 / min Exhaust Gas Temperature ≤750° C



### LEBANON BEIRUT Rachid Karami st, Concorde Center

Rachid Karami st, Concorde Cer Telephone: +9611344518 E-mail: industries@saccal.com

Max

#### UAE SHARJAH Business center, SPC, Telephone: ±9715671

Business center, SPC, Publishing City Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com

ERBIL Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846 +964 77 09887972 E-mail: erbil@saccal.com

IRAQ

BAGHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com



# **BN 825**

****		Genset Large Rang		n STAMFORD power generation
* 1944 *	Engine Fue	el System	Alternator	Specifications
* Since *	Recommended Fuel	Class A2 Diesel	Alternator Make / Model	Stamford Tech 404C
	Fuel Consumption Standby	190.8 L/hr	AVR Model	MX341B
<b>3/155/15</b>	Fuel Consumption @100% PRP	173.7 L/hr	Number of Poles	4
	Fuel Consumption @75% PRP	133.1 L/hr	Number of Winding Leads	6
13	Fuel Consumption @50% PRP	90.8 L/hr	Type of Bearing	Single Bearing
			Excitation System	Self Excited
	cal		Ingress Protection Rating	IP23
	O.		Cooling Airflow	2.18 m3 / Sec
			Voltage Regulation	±0.5%
			Harmonic Coefficient THF	< 2%
			Tel. Influence TIF	< 50
			Insulation Class	Н
Image: Controller	Engine	Alternator	Saccal Encl	osure / Canopy
Controller Make / Model	DeepSea 7320	Canopy Type	SILENT	SUPER SILENT
Operation Mode	Auto-Start & AMF	Enclosure Type	Acoustic & Wea	ather Proof
Display	Graphic Backlit LCD (128x64px)	Drainage	Fuel and Wate	r Drainage Provision
Ingress Protection Rating	IP65	Transportation	Tested Single F Forklift Pocket	Point Lifting Facility &
Binery Inputs/Outputs	4/4	Ingress Protection	IP23	
Analog Inputs	3	Lifting	ISO Standard L	ifting
Measurements	Vac, A, Hz, KVA,KW, Vdc	Canopy RAL Color	RAL 9002 - Pov	vder Coated

Measurements Event Log Alarms Log, Hrs Log Communication

# SACCAL TOOL BOX

### Standard for every GenSet

- Heat Resistant Gloves
- Notebook
- Pen
- Tape Measure
- **Baseball** Cap
- Owner & Operation Manual
- Wiring Diagrams
- Sound Test (Upon Request)

### Why Saccal Generators ?

**Base Frame RAL Color** 

Noise Pressure Level db(A) @ 1m @75% Load

Saccal Industries is one of the leading Diesel Generator OEM firms in the **MENA** Region

With an impressive Factory that spreads over an area of 30 thousand square meters in Bekaa & ISO certification, SACCAL has always been the leading name in the manufacturing and assembly of premium quality generating sets.

From planning and design, construction and production, to local and international sales, Saccal Has more than 80 Years of experience.

### Choose Right - Choose Saccal

SACCAL **INDUSTRIES** 

#### LEBANON BEIRUT Rachid Karami st, Concorde Center Telephone: +9611344518 E-mail: industries@saccal.com

UAE SHARJAH E6 - 024 - Safezone Telephone: +971 56 714 0510 E-mail: Saccaluae@saccal.com IRAQ ERBIL Street 100 - 3/57, Warsh Telephone: +964 78 05416865 +964 75 02194846 +964 77 09887972 E-mail: erbil@saccal.com

BAGHDAD Riyadh District Square - District 908 -Street 25 - House 28 Telephone: +964 77 23813927 E-mail: baghdad@saccal.com

RAL 9005 - Powder Coated

