



**Gensets**  
Large Range

**Perkins**  
THE HEART OF EVERY GREAT MACHINE

**LERROY SOMER**

**Ratings**  
@ 0.8 PF

**50 Hz**  
1500 RPM

VOLTAGE	PRIME RATING	STANDBY RATING
400/3 Ph	730 KVA	800 KVA

## NOTES

### Prime Power

Unlimited hours usage with an average load factor of 75% of the published Prime power over each 24 hours period.

A 10% overload is available for 1 hour in every 12 hour operation.

### Standby Power

Limited to 500 hours annual usage.

Available in 60HZ for all voltage ratings

### Standard Reference Conditions

Note: Standard reference conditions 40°C (104°F) Air inlet temp, 100m (328 ft.) A.S.L. 30% relative humidity.

## Standards Compliance



## Dimensions

	Open Type	Silent	Super Silent
<b>Length:</b>	4230mm	6050mm	6050mm
<b>Width:</b>	1600mm	2440mm	2440mm
<b>Height:</b>	2200mm	2440mm	2440mm
<b>Weight:</b>	6644kg	9250kg	14000kg

## Technical Data

### Diesel Generating Set



<b>GENSET Make / Model</b>	PERKINS 4006-23TAG2A
<b>Alternator Make / Model</b>	Leroy Somer TAL 049B
<b>Control Panel</b>	DSE 7320
<b>Base Frame / Canopy</b>	Robust Structure / Corrosion Resistant
<b>Circuit Breaker Type</b>	3-Pole MCCB (4-Pole Available as option)
<b>Built-In Fuel Tank Capacity (Silent)</b>	N/A
<b>Battery</b>	2x 150 A

### Engine Specifications

<b>Make &amp; Model</b>	PERKINS 4006-23TAG2A
<b>Cylinder &amp; Arrangement</b>	6; Vertical in-line
<b>Cycle</b>	4 stroke
<b>Induction System / Aspiration</b>	Turbocharged
<b>Cooling System</b>	Water cooled
<b>Governing</b>	Electronic
<b>Governing Class</b>	G2 - ISO 8528 Part 1
<b>Compression Ratio</b>	13.6:1
<b>Displacement</b>	22.92l
<b>Bore &amp; Stroke</b>	145 x 183 mm
<b>Dynamic Charging Alternator</b>	55 AMP, 28 V

### Lubrication System

<b>Oil Filter Type</b>	Spin-On Full Flow
<b>Total Oil Capacity</b>	113.4 L
<b>Oil Type</b>	API CI-4

### Cooling System

<b>Total Coolant Capacity</b>	142.0 L	<b>Cooling System Design</b>	50°C
<b>Cooling Fan Air Flow</b>	14.5 m <sup>3</sup> /s	<b>Heat Radiation to Room</b>	79.0 kW
<b>Max Water Temperature</b>	98°C		

### Air System

<b>Air Filter Type</b>	Dry Element
<b>Max Air Filter Intake Restriction</b>	3.7kPa

### Exhaust System

<b>Muffler Type</b>	Industrial Grade
<b>Max Back Pressure</b>	6.0 kPa
<b>Exhaust Gas Flow</b>	180.0 m <sup>3</sup> / min
<b>Exhaust Gas Temperature</b>	≤430° C



**SACCAL INDUSTRIES**

**LEBANON BEIRUT**  
Rachid Karami st, Concorde Center  
Telephone: +961 1 34 45 18  
E-mail: industries@saccal.com

**UAE SHARJAH**  
Business center, SPC, Publishing City  
Telephone: +971 56 714 0510  
E-mail: Saccaluae@saccal.com


**IRAQ ERBIL**  
Street 100 - 3/57, Warsh  
Telephone: +964 78 05416865 +964 75 02194846  
+964 77 09887972 E-mail: erbil@saccal.com

**BAGHDAD**  
Riyadh District Square - District 908 -  
Street 25 - House 28  
Telephone: +964 77 23813927  
E-mail: baghdad@saccal.com





**Controller**



**Engine**



**Alternator**



**Saccal Enclosure / Canopy**

## Engine Fuel System

Recommended Fuel	Class A2 Diesel
Fuel Consumption Standby	176.0 L/hr
Fuel Consumption @100% PRP	160.0 L/hr
Fuel Consumption @75% PRP	124.0 L/hr
Fuel Consumption @50% PRP	87.0 L/hr

## Alternator Specifications

Alternator Make / Model	Leroy Somer TAL 049B
AVR Model	R150
Number of Poles	4
Number of Winding Leads	6
Type of Bearing	Single Bearing
Excitation System	Self Excited
Ingress Protection Rating	IP23
Cooling Airflow	1.00 m <sup>3</sup> / Sec
Voltage Regulation	±0.8%
Harmonic Coefficient THF	< 2%
Tel. Influence TIF	< 50
Insulation Class	H

Controller Make / Model	Deep Sea 7320
Operation Mode	Auto-Start & AMF
Display	Graphic Backlit LCD (128x64px)
Ingress Protection Rating	IP65
Binary Inputs/Outputs	4/4
Analog Inputs	3
Measurements	Vac, A, Hz, KVA, KW, Vdc
Event Log	Alarms Log, Hrs Log
Communication	USB

Canopy Type	SILENT	SUPER SILENT
Enclosure Type	Acoustic & Weatherproof	
Drainage	Fuel and Water Drainage Provision	
Transportation	Tested Single Point Lifting Facility & Forklift Pockets	
Ingress Protection	IP23	
Lifting	ISO Standard Lifting	
Canopy RAL Color	RAL 9002 - Powder Coated	
Base Frame RAL Color	RAL 9005 - Powder Coated	
Noise Pressure Level db(A) @ 1m @ 75% Load	71	65

## SACCAL TOOL BOX

### Standard for every GenSet

- Heat Resistant Gloves
- Notebook
- Pen
- Tape Measure
- Baseball Cap
- Operation Manual
- Wiring Diagrams
- Sound Test (Upon Request)

## Why Saccal Generators ?

**Saccal Industries** is one of the leading diesel generator OEM firms in the **MENA** Region.

With an impressive factory that spreads over an area of 30 thousand square meters in Bekaa & ISO certification, SACCAL has always been the leading name in the manufacturing and assembly of premium quality generating sets.

From planning and design, construction and production, to local and international sales, Saccal has more than 80 Years of experience.

Choose Right - Choose **Saccal**

